

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings of claims in the application:

**Listing of Claims:**

Claim 1. (Currently Amended) A method of determining an implementation of a user design on a programmable device including a plurality of programmable logic elements, each comprising reconfigurable logic hardware and fixed-configuration secondary hardware; the fixed-configuration secondary hardware having a plurality of inputs, the inputs common to at least two of the programmable logic elements, the method comprising:

~~determining a plurality of assignments~~ for each of a plurality of portions of the user design, determining one or more sets of input assignments to the fixed-configuration secondary hardware, each set providing an implementation of that portion of the user design using the fixed-configuration secondary hardware of a programmable logic element;

ranking the ~~plurality of input~~ assignments by determining a number of times each of a plurality of signals in the user design is assigned as a respective input one of the plurality of ~~inputs~~ to the fixed-configuration secondary hardware; ~~and~~

selecting the highest ranked input assignment, where a first signal in the plurality of signals in the user design is assigned as a first input ~~of the plurality of inputs~~ to the fixed-configuration secondary hardware more than any other signal signals in the plurality of signals in the user design are ~~is~~ assigned to an input to the fixed-configuration secondary hardware; and

implementing the user design by implementing the first signal as the first input ~~of the plurality of inputs~~ to the fixed-configuration secondary hardware.

Claim 2. (Currently Amended) The method of claim 1, wherein each of the ~~plurality of input~~ assignments defines an assignment of at least one input variable of the user design to an input of the fixed-configuration secondary hardware.

Claim 3. (Original) The method of claim 1, wherein the fixed-configuration secondary hardware enables load and clear functions of a register of the programmable device.

Claim 4. (Currently Amended) The method of claim 1, wherein each set of the ~~plurality of input~~ assignments is associated with at least one register of the user design.

Claim 5. (Currently Amended) The method of claim 4, wherein ranking the ~~plurality of input~~ assignments includes determining ~~the a~~ number of registers of the user design associated with each input assignment ~~of the plurality of assignments~~.

Claim 6. (Currently Amended) The method of claim 5, wherein selecting the highest ranked input assignment includes selecting the input assignment with the most associated registers ~~from the plurality of assignments~~.

Claim 7. (Currently Amended) The method of claim 4, comprising disassociating at least one register from at least one of the ~~plurality of input~~ assignments, wherein the disassociated register is associated with the selected input assignment.

Claim 8. (Currently Amended) The method of claim 1, comprising removing the selected input assignment from the ~~plurality of input~~ assignments, thereby forming a subset of the ~~plurality of input~~ assignments.

Claim 9. (Currently Amended) The method of claim 8, comprising evaluating a criteria for the subset of the ~~plurality of input~~ assignments; and  
in response to a determination that the criteria exceeds a threshold, reiterating the steps of ~~determining a plurality of assignments~~, ranking the plurality of assignments; and selecting the highest ranked input assignment for the subset of the ~~plurality of input~~ assignments.

Claim 10. (Currently Amended) The method of claim 2, wherein determining one or more sets of input assignments ~~a plurality of assignments~~ comprises:  
enumerating a plurality of sets of input variables associated with the portion of the user design; and  
creating a plurality of input assignments from at least a portion of the sets of input variables.

Claim 11. (Previously Presented) The method of claim 10, further comprising:

creating a logic diagram describing the function of each of the plurality of sets of input variables; and

determining from the logic diagram whether the function of each of the plurality of sets of input variables corresponds with at least one function of the fixed-configuration secondary hardware.

Claim 12 (Original) The method of claim 11, wherein the logic diagram is a truth table.

Claim 13. (Original) The method of claim 11, wherein the logic diagram is a Karnaugh map.

Claim 14. (Currently Amended) The method of claim 11, wherein creating a plurality of input assignments comprises applying at least one heuristic to each of the plurality of sets of input variables having a function corresponding with at least one function of the fixed-configuration secondary hardware, thereby determining at least one corresponding assignment.

Claim 15. (Original) The method of claim 10, wherein enumerating a plurality of sets of input variables includes using cut enumeration.

Claims 16-19. (Cancelled)

Claim 20. (Currently Amended) An information storage medium including a set of instructions adapted to operate an information processing device to perform a set of steps to implement a user design on an integrated circuit, the integrated circuit comprising a plurality of programmable logic elements, each comprising fixed-configuration secondary hardware, the set of steps comprising:

~~determining a plurality of assignments~~ for each of a plurality of portions of the user design, determining one or more sets of input assignments to the fixed-configuration

secondary hardware, each set providing an implementation of that portion of the user design  
using the fixed-configuration secondary hardware ~~of a programmable logic element;~~

ranking the ~~plurality of input~~ assignments by determining a number of times each  
of a plurality of signals in the user design is assigned as a respective input ~~one of the plurality of~~  
~~inputs~~ to the fixed-configuration secondary hardware; and

selecting the highest ranked input assignment, where a first signal in the plurality  
of signals in the user design is assigned as a first input ~~of the plurality of inputs~~ to the fixed-  
configuration secondary hardware more than any other signal ~~signals in the plurality of signals in~~  
the user design ~~are~~ is assigned to an input to the fixed-configuration secondary hardware; and

implementing the user design by implementing the first signal as the first input ~~of~~  
~~the plurality of inputs~~ to the fixed-configuration secondary hardware.

Claim 21. (Currently Amended) The information storage medium of claim  
20, wherein each of the ~~plurality of input~~ assignments defines an assignment of at least one input  
variable of the user design to an input of the fixed-configuration secondary hardware.

Claim 22. (Original) The information storage medium of claim 20, wherein  
the fixed-configuration secondary hardware enables load and clear functions of a register of the  
programmable device.

Claim 23. (Currently Amended) The information storage medium of claim  
20, wherein each set of the ~~plurality of input~~ assignments is associated with at least one register  
of the user design.

Claim 24. (Currently Amended) The information storage medium of claim  
23, wherein ranking the ~~plurality of input~~ assignments includes determining ~~the a~~ number of  
registers of the user design associated with each input assignment ~~of the plurality of assignments~~.

Claim 25. (Currently Amended) The information storage medium of claim  
24, wherein selecting the highest ranked input assignment includes selecting the input  
assignment with the most associated registers ~~from the plurality of assignments~~.

Claim 26. (Currently Amended) The information storage medium of claim 23, comprising disassociating at least one register from at least one of the ~~plurality of~~ input assignments, wherein the disassociated register is associated with the selected input assignment.

Claim 27. (Currently Amended) The information storage medium of claim 20, comprising removing the selected input assignment from the ~~plurality of~~ input assignments, thereby forming a subset of the ~~plurality of~~ input assignments.

Claim 28. (Currently Amended) The information storage medium of claim 27, comprising evaluating a criteria for the subset of the ~~plurality of~~ input assignments; and  
in response to a determination that the criteria exceeds a threshold, reiterating the steps of ~~determining a plurality of assignments~~, ranking the plurality of assignments; and selecting the highest ranked input assignment for the subset of the ~~plurality of~~ input assignments.

Claim 29. (Currently Amended) The information storage medium of claim 21, wherein determining one or more sets of input assignments ~~a plurality of assignments~~ comprises:

enumerating a plurality of sets of input variables associated with the portion of the user design; and

creating a plurality of input assignments from at least a portion of the sets of input variables.

Claim 30. (Previously Presented) The information storage medium of claim 29, further comprising:

creating a logic diagram describing the function of each of the plurality of sets of input variables; and

determining from the logic diagram whether the function of each of the plurality of sets of input variables corresponds with at least one function of the fixed-configuration secondary hardware.

Claim 31 (Original) The information storage medium of claim 30, wherein the logic diagram is a truth table.

Claim 32. (Original) The information storage medium of claim 30, wherein the logic diagram is a Karnaugh map.

Claim 33. (Currently Amended) The information storage medium of claim 30, wherein creating a plurality of input assignments comprises applying at least one heuristic to each of the plurality of sets of input variables having a function corresponding with at least one function of the fixed-configuration secondary hardware, thereby determining at least one corresponding assignment.

Claim 34. (Original) The information storage medium of claim 29, wherein enumerating a plurality of sets of input variables includes using cut enumeration.

Claim 35. (Cancelled)

Claim 36. (Previously Presented) A method of implementing a user design on an integrated circuit, the user design comprising a plurality of logic gates and a plurality of registers, the integrated circuit comprising a plurality of programmable logic elements, each programmable logic element comprising a register and a plurality of logic gates having a plurality of inputs, the method comprising:

for each register in the plurality of registers in the user design:

determining a logic representation for at least one logic gate having a plurality of inputs, the at least one logic gate coupled to the input of the register in the user design;

determining at least one way to implement the logic representation using the plurality of logic gates in a programmable logic element; and

assigning input signals to the at least one logic gate of the user design to inputs of the logic gates in the programmable logic element; then

for each input signal in a plurality of input signals to the logic gates coupled to input of registers in the user design:

determining a number of occurrences where the input signal is assigned to an input of the logic gates in a programmable logic element; and

determining a first input signal and first input of the logic gates in the programmable logic elements where the first input signal is assigned to the first input more than other input signals are assigned to an input of the logic gates in the programmable logic elements; then

implementing the user design on the integrated circuit by implementing the first input signal as the first input of the logic gates in the programmable logic elements.

Claim 37. (Previously Presented) The method of claim 36 wherein the logic gates provide load and clear functions for the register in a programmable logic element.